


# DOMESTIC Openwell Submesible Pump



## SELECTION CHART FOR ACUBE Domestic Horizontal Openwell Submersible Pumpset

Performance Chart at 2900 rpm, 230V SINGLE PHASE 380V, Three phase, 50 Hz A.C. supply

SR. NO.	MODEL	SUC X DEL (MM)	MOTOR RATING			HEAD IN METER							
			H.P	K.W	PHASE	6	9	13	18	22	26	28	32
1	APOD0570	25X25	0.5	0.37	1	190	160	135	60	10	-	-	-
2	APOD10100	25X25	1.0	0.75	1	254	210	180	115	75	30	-	-
3	APOD15110	40X40	1.5	1.12	1	387	304	254	210	189	112	-	-
4	APOD20110	50X50	2.0	1.5	1	502	437	344	287	209	146	-	-
5	APODS30115	65X50	3.0	2.25	1	724	687	480	389	284	169	-	-
6	APODS3090	65X65	3.0	2.25	1	880	725	540	380	295	145	-	-
7	APODT30110	65X50	3.0	2.25	3	724	687	480	389	284	169	-	-
8	APODT3090	65X65	3.0	2.25	3	780	725	540	380	295	145	-	-
9	APODS50115	65X50	5.0	3.75	1	820	687	560	475	381	295	174	-
10	APODS50100	65X65	5.0	3.75	1	940	825	654	425	310	195	-	-
11	APODT50115	65X50	5.0	3.75	3	820	687	560	475	381	295	174	-
12	APODT50100	65X65	5.0	3.75	3	940	825	654	425	310	195	-	-