


# 130mm (V5) Submersible Pumpsets(DELUXE)



## SELECTION CHART FOR ACUBE (130 MM) 5" SUBMERSIBLE S.S PUMP SETS


Pumpsets suitable for 130 mm borewell size or above (Min.Bore dia-130mm)  
Performance Chart at 2900 rpm, 415V three phase, 50 Hz A.C. supply

105 LPM SERIES		OUTLET SIZE :50 MM		2900 RPM							
MODEL CODE	STG	MOTOR RATING		DISCHARGE							
		H.P.	K.W.	LPM	60	80	95	105	115	125	150
AP5S3010	10	3	2.25	Head Meters	110	100	90	80	70	60	40
AP5S4013	13	4	3.0		143	130	117	104	91	77	52
AP5S5016	16	5	3.75		176	160	144	128	112	96	64
AP5S6020	20	6	4.5		220	200	180	160	140	120	80
AP5S7525	25	7.5	5.6		275	250	225	200	175	150	100
AP5S1033	33	10	7.5		363	330	297	264	231	198	172

130 LPM SERIES		OUTLET SIZE :50 MM		2900 RPM							
MODEL CODE	STG	MOTOR RATING		DISCHARGE							
		H.P.	K.W.	LPM	80	100	115	130	140	150	182
AP5S3007	7	3	2.25	Head Meters	77	70	63	56	49	42	28
AP5S4010	10	4	3.0		110	100	90	80	70	60	40
AP5S5012	12	5	3.75		132	120	108	96	84	72	48
AP5S6015	15	6	4.5		165	150	135	120	105	90	60
AP5S7519	19	7.5	5.6		209	190	171	152	133	114	76
AP5S1025	25	10	7.5		275	250	225	200	175	150	100

180 LPM SERIES		OUTLET SIZE :50 MM		2900 RPM							
MODEL CODE	STG	MOTOR RATING		DISCHARGE							
		H.P.	K.W.	LPM	80	120	155	185	205	230	260
AP5S3006	6	3	2.25	Head Meters	66	60	54	48	42	36	24
AP5S4008	8	4	3.0		88	80	72	64	56	48	32
AP5S5010	10	5	3.75		110	100	90	80	70	60	40
AP5S6012	12	6	4.5		132	120	108	96	84	72	48
AP5S7515	15	7.5	5.6		165	150	135	120	105	90	60
AP5S1020	20	10	7.5		220	200	180	160	140	120	80

# 130mm (V5) Submersible Pumpsets(DELUXE)



## SELECTION CHART FOR ACUBE (130 MM) 5" SUBMERSIBLE S.S PUMP SETS

Pumpsets suitable for 130 mm borewell size or above (Min.Bore dia-130mm)  
Performance Chart at 2900 rpm, 415V three phase, 50 Hz A.C. supply

105 LPM SERIES		OUTLET SIZE :50 MM		2900 RPM							
MODEL CODE	STG	MOTOR RATING		DISCHARGE							
		H.P.	K.W.	LPM	60	80	95	105	115	125	150
AP5S3010	10	3	2.25	Head Meters	110	100	90	80	70	60	40
AP5S4013	13	4	3.0		143	130	117	104	91	77	52
AP5S5016	16	5	3.75		176	160	144	128	112	96	64
AP5S6020	20	6	4.5		220	200	180	160	140	120	80
AP5S7525	25	7.5	5.6		275	250	225	200	175	150	100
AP5S1033	33	10	7.5		363	330	297	264	231	198	172

130 LPM SERIES		OUTLET SIZE :50 MM		2900 RPM							
MODEL CODE	STG	MOTOR RATING		DISCHARGE							
		H.P.	K.W.	LPM	80	100	115	130	140	150	182
AP5S3007	7	3	2.25	Head Meters	77	70	63	56	49	42	28
AP5S4010	10	4	3.0		110	100	90	80	70	60	40
AP5S5012	12	5	3.75		132	120	108	96	84	72	48
AP5S6015	15	6	4.5		165	150	135	120	105	90	60
AP5S7519	19	7.5	5.6		209	190	171	152	133	114	76
AP5S1025	25	10	7.5		275	250	225	200	175	150	100

180 LPM SERIES		OUTLET SIZE :50 MM		2900 RPM							
MODEL CODE	STG	MOTOR RATING		DISCHARGE							
		H.P.	K.W.	LPM	80	120	155	185	205	230	260
AP5S3006	6	3	2.25	Head Meters	66	60	54	48	42	36	24
AP5S4008	8	4	3.0		88	80	72	64	56	48	32
AP5S5010	10	5	3.75		110	100	90	80	70	60	40
AP5S6012	12	6	4.5		132	120	108	96	84	72	48
AP5S7515	15	7.5	5.6		165	150	135	120	105	90	60
AP5S1020	20	10	7.5		220	200	180	160	140	120	80